

Model Number 039230-51015/B		ROTARY TORQUE, W/ENCODER AND AUTO ID			Revision: NR ECN #: 47364											
Performance		ENGLISH	SI		OPTIONAL VERSIONS											
Measurement Range(Full Scale Capacity)	132 lbf-in	15 Nm			Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.											
Sensitivity(output at rated capacity)	2.0 mV/V	2.0 mV/V	[7]													
Non-Linearity	≤ 0.25 % FS	≤ 0.25 % FS	[2]													
Hysteresis	≤ 0.25 % FS	≤ 0.25 % FS	[2]													
Non-Repeatability	≤ 0.05 % FS	≤ 0.05 % FS	[2]													
Interchangeability	≤ 0.30 % FS	≤ 0.30 % FS	[8][2]													
Environmental																
Overload Limit	203 lbf-in	23 Nm			NOTES: [1] Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS. [2] FS - Full Scale. [3] Magnetic Encoder Specifications. [4] A-B Track 90° Phase Difference, Flat Over Operating Speed [5] Matched with 43.575 kOhm Precision Resistor. [6] Over compensated temperature range. [7] Matched to ±0.25% F.S. [8] Matched for mV/V and shunt calibration. [9] See Outline Drawing 45188 for Complete Dimensions [10] Per ANSI B107.4 Specifications [11] See PCB Declaration of Conformance PS119 for details.											
Temperature Range(Operating)	0 to +200 °F	-18 to +93 °C														
Temperature Range(Compensated)	+70 to +150 °F	+21 to +66 °C														
Temperature Effect on Output(Maximum)	± 0.002 %Reading/°F	± 0.0018 %Reading/°C	[6]													
Temperature Effect on Zero Balance(Maximum)	± 0.002 %FS/°F	± 0.0018 %FS/°C	[6]													
Electrical																
Bridge Resistance	350 Ohm	350 Ohm			SUPPLIED ACCESSORIES: Model 7122R-04352A PRECISION CAL RESISTOR 43.575 kOhm											
Excitation Voltage	10 VDC	10 VDC	[1]													
Insulation Resistance	≥ 5 GOhm	≥ 5 GOhm														
Zero Balance	≤ 2 % FS	≤ 2 % FS	[2]													
Counts Per Revolution	1472	1472	[3]													
Resolution w/ Quadrature	1/4 °	1/4 °	[3]		OPTIONAL ACCESSORIES: Model 080920-01000 Model 920 Portable Digital Peak Meter for torque, torque-angle or load measurement; Click-Wrench calc feature, w/battery charger, instruction manual & shoulder strap Model 080962-01000 MODEL 962 DATA RECORDER Model 097000-34445 INTERCONNECT CABLE Model 4242R-000630 MATING CONNECTOR PT06A-12-10S(SR)											
Output Voltage	High 5V to Low 0.5V	High 5V to Low 0.5V	[3]													
Power Required(maximum)	5 VDC @ 120mA	5 VDC @ 120mA	[3]													
Magnetic Encoder(Poles)	360	360	[3]													
Magnetic Encoder(Ouput)	See Note	See Note	[4][3]													
Shunt Calibration	≤ 0.25 % FS	≤ 0.25 % FS	[5][2]													
Auto ID	TTL Proprietary	TTL Proprietary														
Physical																
Size (Shaft Length x Housing Length x Housing Height)	4.25 in x 2.30 in x 2.00 in	108.0 mm x 58.4 mm x 50.8 mm	[9]		<table><tr><td>Entered: LK</td><td>Engineer: PE</td><td>Sales: DM</td><td>Approved: JSD</td><td>Spec Number:</td></tr><tr><td>Date: 10/31/2017</td><td>Date: 10/31/2017</td><td>Date: 10/31/2017</td><td>Date: 10/31/2017</td><td>68199</td></tr></table>		Entered: LK	Engineer: PE	Sales: DM	Approved: JSD	Spec Number:	Date: 10/31/2017	Date: 10/31/2017	Date: 10/31/2017	Date: 10/31/2017	68199
Entered: LK	Engineer: PE	Sales: DM	Approved: JSD	Spec Number:												
Date: 10/31/2017	Date: 10/31/2017	Date: 10/31/2017	Date: 10/31/2017	68199												
Weight	.75 lb	340 gm														
Mounting	1/4 inch Hex Drive	6.35 mm Hex Drive	[10]													
Sensing Element	Strain Gage	Strain Gage														
Housing Material	Aluminum	Aluminum			 [11] All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.											
Shaft Material	Steel	Steel														
Electrical Connector	PT02H-12-10P	PT02H-12-10P														
Maximum Speed	5000 RPM	5000 RPM														