



Industrial Electronics



LEAK-DETECT
**Leakage Detecting Device for Compressed
Air Ring Mains and Pneumatic Systems**



Hilger u. Kern

LEAK-DETECT

LEAK-DETECT is a specialised development from Hilger u. Kern Industrial electronics.

This device is able to detect even the smallest leaks in compressed air systems.

These types of leaks are a typical source of non-audible ultrasonic sound, but at a defined frequency. LEAK-DETECT is a reliable detector which converts this sound into an audible signal and optically displays the signal level on a LED-bar.

LEAK-DETECT can be used to locate leaks in

- compressed air ring mains and all kinds of pneumatic systems
- vacuum equipment
- valves and fittings
- steam tubes
- oxygen sockets in hospitals
- air conditioning systems in automotive vehicles

Features and Benefits

- Easy to handle
- Immediately ready for use
- Offers a systematic detection of leaks
- Reduces running costs and consumption of compressed air*
- Increases the reliability of pneumatic systems*
- Checking door and window seals of cars, pressure containers, ships, trucks, buses, trains, aeroplanes etc.*

* for further details please download the newsletter at www.hilger-kern.com in the product segment Industrial Electronics/Newsletter

Equipment

Standard

- LEAK-DETECT
- Ultrasonic probe, length 110 mm
- Detection probe for focusing on small leaks from screw threads and fittings
- Headset with hygienic protectors
- 9 V battery
- Rugged ABS portable case

Optional

- Telescopic rod, 1.50 m long, extendable to 3.00 m
- Parabolic dish with laserpointer
- 9 V accumulator with charger
- Ultrasonic transmitter for leakage check without compressed air



Function

The source is ultrasonic sound

The flow characteristics of leaking gases are a typical source of non-audible ultrasonic sound, but at a defined frequency.

LEAK-DETECT converts this sound into an audible signal in the headset and displays the signal level as an LED-bar.

Checking for airtight seals

The combination of a LEAK-DETECT receiver with an optional transmitter makes it possible to check that seals in vehicle cabins, cockpits, refrigerators, housings, etc. are airtight.

1. Place the transmitter inside the cabin and switch the power on.
2. Close the housing or cabin.
3. Switch on the LEAK-DETECT device.
4. Use the LEAK-DETECT sensor to scan the seals to find any leaks while moving the probe along the seals.




Trace the leakage

1. Plug in the ultrasonic probe, the telescopic rod or the parabolic dish. Plug into the 9 pole sub-D plug of the electronic device.
2. Plug in and put on the head set.
3. Switch on the power. A green LED will indicate that the battery is full.
4. Adjust the hissing in the head set by pressing the „+“ or „-“ key.
5. Direct the sensor to the area of equipment that needs to be checked. These areas are normally tubes, fittings and screws. For longer distances, the laserpointer inside the parabolic dish is a helpful direction finder (optional) .
6. A leak has been detected if the audio signal increases and the LED signal moves into the red area.

Technical Data

Power supply	9 V battery or accumulator
Ultrasonic probe	110 mm gooseneck
Telescopic rod length	1.5 to 3.0m length, 25 mm Ø
Parabolic dish	380 mm Ø
Signal output	LED-bar indicator
Dimensions LEAK-DETECT	180 x 90 x 60 mm
Weight	250 g
Dimensions portable case	360 x 305 x 110 mm
Weight incl. portable case	1500 g
Protection class	IP 67
Housing material	ABS with electromagnetic shield
Operation temperature	0 bis +55 °C
Approval mark	CE (tested against electromagnetic disturbances and emissions)



Leak detection on distance

Function

We recommend to use the longer gooseneck probe or even a telescopic rod for difficult or inaccessible locations.

A further feature for longer distances is the parabolic dish with integrated ultrasonic sensor and laserpointer.


The integrated laserpointer makes it easy to trace leaks over distances from 20 m to more than 100 m for bigger leaks.

The parabolic dish is made of transparent plastic, so that the leaks are easily visible.

All incoming ultrasonic waves are reflected from the dish and focused at the ultrasonic receiver. Noise is ignored.



Hilger u. Kern / Dopag Group



Hilger u. Kern GmbH

Käfertaler Straße 253
68167 Mannheim
Germany

☎ +49 621 3705-0
☎ +49 621 3705-200

info@hilger-kern.de
www.hilger-kern.com

DOPAG Dosiertechnik
und Pneumatik AG

Langackerstrasse 25
6330 Cham
Schweiz

☎ +41 41 7855-757
☎ +41 41 7855-700

info@dopag.ch
www.dopag.com

Drive Technology

☎ +49 621 3705-316
☎ +49 621 3705-403
antriebstechnik@hilger-kern.de

Metering Technology

☎ +49 621 3705-263
☎ +49 621 3705-271
dosiertechnik@hilger-kern.de

Industrial Electronics

☎ +49 621 3705-294
☎ +49 621 3705-402
industriielektronik@hilger-kern.de

Vibration Technology

☎ +49 621 3705-249
☎ +49 621 3705-402
schwingungstechnik@hilger-kern.de

Spray Technology

☎ +49 621 3705-293
☎ +49 621 3705-271
spritztechnik@hilger-kern.de

The Hilger u. Kern / Dopag Group, with more than 250 employees, 7 subsidiaries and 24 distributors, is one of the leading manufacturers of metering and mixing systems in the world for plural component polymers and single component media such as greases, oils and pastes. For more than 35 years the group has developed systems and components to suit your individual needs. Hilger u. Kern Mannheim, with its Drive Engineering, Metering Systems, Industrial Electronics and Spray Technology divisions, is one of the leading Manufacturers of high-quality and innovative technical capital goods in Germany.