

	ENGLISH	SI	
<b>Performance</b>			
Measurement Range (for ±5V output)	500 psi	3448 kPa	
Useful Overrange (for ± 10V output)	1 kpsi	6895 kPa	[1]
Sensitivity (±1.0 mV/psi)	10 mV/psi	1.45 mV/kPa	
Maximum Pressure (static)	5 kpsi	34475 kPa	
Resolution	10 mpsi	0.07 kPa	
Resonant Frequency	≥400 kHz	≥400 kHz	
Rise Time (Reflected)	≤1.5 μ sec	≤1.5 μ sec	
Low Frequency Response (-5 %)	0.01 Hz	0.01 Hz	
Non-Linearity	≤2.0 % FS	≤2.0 % FS	[2]
<b>Environmental</b>			
Acceleration Sensitivity	<0.002 psi/g	<0.0014 kPa/(m/s <sup>2</sup> )	
Temperature Range (Operating)	-100 to +275 °F	-73 to +135 °C	
Temperature Coefficient of Sensitivity	≤0.2 %/°F	≤0.36 %/°C	
Maximum Vibration	2000 g pk	19614 m/s <sup>2</sup> pk	
Maximum Shock	20000 g pk	196140 m/s <sup>2</sup> pk	
<b>Electrical</b>			
Output Polarity (Positive Pressure)	Positive	Positive	
Discharge Time Constant (at room temp)	≥50 sec	≥50 sec	
Excitation Voltage	20 to 30 VDC	20 to 30 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	≤100 Ohm	≤100 Ohm	
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC	
<b>Physical</b>			
Sensing Geometry	Compression	Compression	
Sensing Element	Quartz	Quartz	
Housing Material	17-4 Stainless Steel	17-4 Stainless Steel	
Diaphragm	Invar	Invar	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Weight	0.21 oz	6.0 gm	



All specifications are at room temperature unless otherwise specified.  
 In the interest of constant product improvement, we reserve the right to change specifications without notice.  
 ICP® is a registered trademark of PCB group, Inc.

**Optional Versions** (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.)

<b>E</b> - Emralon coating			[4]
Coating	Emralon	Emralon	
Electrical Isolation	10 <sup>8</sup> Ohm	10 <sup>8</sup> Ohm	
Supplied Accessory: Model 065A08 Isolation ring, 0.250" OD x 0.218" ID x 0.027" thk, anodized aluminum			
Supplied Accessory: Model 065A22 Isolation Seal, .250" OD x .218" ID x .015", Torton or Vespel			
<b>H</b> - Hermetic Seal			[4]
Sealing	Welded Hermetic	Welded Hermetic	
<b>J</b> - Ground Isolated			[4]
			[5]
<b>N</b> - Negative Output Polarity			[4]
<b>S</b> - Stainless Steel Diaphragm			[4]
Diaphragm	316L Stainless Steel	316L Stainless Steel	
<b>W</b> - Water Resistant Cable			[4]

**Notes**

- [1] For +10 volt output, minimum 24 VDC supply voltage required. Negative 10 volt output may be limited by output bias.
- [2] Zero-based, least-squares, straight line method.
- [3] See PCB Declaration of Conformance PS023 for details.
- [4] For sensor mounted in thread adaptor, see adaptor installation drawing for supplied accessories.
- [5] Used with optional mounting adaptor.

**Supplied Accessories**

- 060A03 Clamp nut, 5/16-24-2A thd, 1/4" hex, stainless steel (1)
- 060A05 Clamp nut M7 x 0.75-6g thd (1)
- 065A02 Seal ring, sensor flush mount, 0.248" OD x 0.219" ID x 0.015" thk, brass (3)
- 065A05 Seal sleeve sensor recess mount 0.248" OD x 0.221" ID x 0.240" thk 17-4 (1)

Entered: AP	Engineer: MJK	Sales: KWW	Approved: BAM	Spec Number:
Date: 03/19/2013	Date: 03/19/2013	Date: 03/19/2013	Date: 03/19/2013	<b>5714</b>



3425 Walden Avenue  
 Depew, NY 14043  
 UNITED STATES  
 Phone: 800-828-8840  
 Fax: 716-684-0987  
 E-mail: info@pcb.com  
 Web site: www.pcb.com