



Model Number 112A22	PRESSURE SENSOR, ICP®		Revision H ECN #: 40791										
Performance Measurement Range (for ±5V output) Useful Overrange (for ± 10V output) Sensitivity (±15 %) Maximum Pressure Resolution Resonant Frequency Rise Time Low Frequency Response (-5 %) Non-Linearity	ENGLISH 50 psi 100 psi 100 mV/psi 500 psi 1 mpsi ≥250 kHz ≤2.0 µ sec 0.50 Hz ≤1.0 % FS	SI 345 kPa 690 kPa 14.5 mV/kPa 3450 kPa 0.007 kPa ≥250 kHz ≤2.0 µ sec 0.50 Hz ≤1.0 % FS	Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.) E - Emralon coating [4] Coating Emralon Emralon Electrical Isolation 10 ⁸ Ohm 10 ⁸ Ohm Supplied Accessory: Model 065A08 Isolation ring, 0.250" OD x 0.218" ID x 0.027" thk, anodized aluminum Supplied Accessory: Model 065A22 Isolation Seal, .250" OD x .218" ID x .015", Torton or Vespel H - Hermetic Seal [4] Sealing Welded Hermetic Welded Hermetic J - Ground Isolated [4] N - Negative Output Polarity [4] S - Stainless Steel Diaphragm [4] Diaphragm 316L Stainless Steel 316L Stainless Steel W - Water Resistant Cable [4] Supplied Accessory: Model 060A03 Clamp nut, 5/16-24-2A thd, 1/4" hex, stainless steel (for Series 111, 112 and 113) [6] WM - Water Resistant Cable [4] Supplied Accessory: Model 060A05 Clamp nut, M7 x 0.75-6G thd (for Series 111, M112 and M113) [6]										
Environmental Acceleration Sensitivity Temperature Range (Operating) Temperature Coefficient of Sensitivity Maximum Flash Temperature Maximum Shock	≤0.002 psi/g -100 to +275 °F ≤0.06 %/°F 3000 °F 20000 g pk	≤0.0014 kPa/(m/s ²) -73 to +135 °C ≤0.108 %/°C 1650 °C 196000 m/s ² pk											
Electrical Output Polarity (Positive Pressure) Discharge Time Constant (at room temp) Excitation Voltage Constant Current Excitation Output Impedance Output Bias Voltage	Positive ≥1.0 sec 22 to 30 VDC 2 to 20 mA <100 Ohm 8 to 14 VDC	Positive ≥1.0 sec 22 to 30 VDC 2 to 20 mA <100 Ohm 8 to 14 VDC											
Physical Sensing Geometry Sensing Element Housing Material Diaphragm Sealing Electrical Connector Weight (with clamp nut)	Compression Quartz 17-4 Stainless Steel Invar Welded Hermetic 10-32 Coaxial Jack 0.21 oz	Compression Quartz 17-4 Stainless Steel Invar Welded Hermetic 10-32 Coaxial Jack 6.0 gm	Notes [1] For +10 volt output, minimum 24 VDC supply voltage required. Negative 10 volt output may be limited by output bias. [2] Zero-based, least-squares, straight line method. [3] See PCB Declaration of Conformance PS023 for details. [4] For sensor mounted in thread adaptor, see adaptor installation drawing for supplied accessories. [5] Used with optional mounting adaptor. [6] Clamp nut installed prior to cable attachment										
 [3]	Supplied Accessories 060A03 Clamp nut, 5/16-24-2A thd, 1/4" hex, stainless steel (1) 060A05 Clamp nut M7 x 0.75-6g thd (1) 065A02 Seal ring, sensor flush mount, 0.248" OD x 0.219" ID x 0.015" thk, brass (3) 065A05 Seal sleeve sensor recess mount 0.248" OD x 0.221" ID x 0.240" thk 17-4 (1)												
<i>All specifications are at room temperature unless otherwise specified.</i> In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB group, Inc.	<table border="1" data-bbox="1129 1271 2011 1347"> <tr> <td>Entered: AP</td> <td>Engineer: MJK</td> <td>Sales: KWW</td> <td>Approved: BAM</td> <td>Spec Number:</td> </tr> <tr> <td>Date: 03/19/2013</td> <td>Date: 03/19/2013</td> <td>Date: 03/19/2013</td> <td>Date: 03/19/2013</td> <td>6476</td> </tr> </table>			Entered: AP	Engineer: MJK	Sales: KWW	Approved: BAM	Spec Number:	Date: 03/19/2013	Date: 03/19/2013	Date: 03/19/2013	Date: 03/19/2013	6476
Entered: AP	Engineer: MJK	Sales: KWW	Approved: BAM	Spec Number:									
Date: 03/19/2013	Date: 03/19/2013	Date: 03/19/2013	Date: 03/19/2013	6476									
	 3425 Walden Avenue Depew, NY 14043 UNITED STATES Phone: 800-828-8840 Fax: 716-684-0987 E-mail: info@pcb.com												

